

## magicolor 5430 DL



Fast, affordable color laser printer for small businesses and workgroups Up to 21 ppm color and black & white 2400 dpi resolution 10/100BaseTX Ethernet® and Hi-Speed USB interfaces

### Extreme color for the business on the move







#### **Take Printing to the Extreme**

Get extreme speed and bold, high-impact color with the magicolor® 5430 DL from KONICA MINOLTA. It pumps out pages at up to 21 ppm and makes challenging jobs look so easy. Plus it's equipped with network-ready gear and a quick set up package. All at an extremely good price.

#### **Working for You**

- The magicolor 5430 DL prints pages extremely fast—up to 21 ppm in both color and black & white.
- Built-in 10/100BaseTX Ethernet® and high-speed USB interfaces mean you can share the value of the magicolor 5430 DL throughout the office.
- With its fast speed and low cost, the magicolor
  5430 DL can easily become your office standard, replacing color inkjet and black-&-white printers.

### **Easy Does It**

- All-in-one toner cartridges mean fewer supplies to order and replace. They're pre-installed for quick set-up and color coded for easy replacement.
- Conveniently check remaining toner levels from the printer's front keypad and view how much paper remains with a quick glance at the input cassette.

#### **Express Yourself**

- The magicolor 5430 DL prints 2400 x 600 dpi on plain paper, labels, envelopes, transparencies, glossy and thick paper—so all your office projects will look great.
- Everything you print, from business reports and correspondence to digital photos and flyers, will stand out with color appeal thanks to the printer's 2400 x 600 dpi print quality.



magicolor 5430 DL



magicolor 5430 DL with optional 500-sheet lower input feeder and duplexer





## basics

# options

#### Front Keypad

- Intuitive display & menu
- At-a-glance toner gauges

#### **Print speed**

- Color: up to 21 ppm
- B&W: up to 21 ppm

#### Interfaces

■ Ethernet (10/100BaseTX), Hi-Speed USB 2.0

#### Memory

■ 64 MB RAM

#### Compatibility

- Windows® Server 2003/XP/ 2000/NT 4/Me/98SE
- Mactintosh® OSX
- Linux Red Hat 8.0, SuSE 8.1+

#### Paper size and input

- Up to letter (8.5" x 11")
- 250-sheet cassette
- Quick-view paper level indicator



#### Memory

• Upgrade to 576 MB

#### **Document handling**

 Automatic duplexer for two-sided printing

#### Paper input

- 500-sheet lower input feeder (add up to two)
- Adds legal (8.5" x 14") support
- 1,250-sheet maximum input capacity









**PAGESCOPE** 

D-SHOP.com

### magicolor 5430 DL - Technical

#### **Printing Process**

Print Method: electrophotographic laser

Print Speed:

Color: up to 21 ppm Monochrome: up to 21 ppm First Page Output Time:

Color: 14.1 seconds from an idle, ready state Monochrome: 14.1 seconds from an idle, ready state

(Exact print speed differs depending on system configuration, software application, driver, and document complexity)

**Resolution:** 2400 x 600 dpi, 1200 x 600 dpi (default), 600 x 600 dpi Recommended Duty Cycle: Up to 60,000 prints/month



Processor Type: ARM9, 200 MHz

Memory: 64 MB SDRAM on board, upgradeable to 576 MB (one slot) Operating System Compatibility: Windows Server 2003/XP/2000/NT4/ Me/98SE; Macintosh OSX (v10.2+); Linux Red Hat 8.0, SuSE 8.1+ **Printer Management:** PageScope $^{\text{\tiny M}}$  Web Connection; driver support for

Windows and Macintosh; Status Monitor (Windows only) Color Support: Enhanced Automatic Image Density Control (eAIDC), Automatic ICC-based color matching, ICC device profiles

#### **Host System Requirements**

Windows:

Minimum: 400 MHz Pentium® II-class PC with 256 MB free disk space, 128 MB RAM, and a 1x or faster CD-ROM / DVD drive

Recommended: 500 MHz or higher Pentium III-class PC

Minimum: Power Mac G3 with 256 MB free disk space and a 1x or faster

CD-ROM / DVD drive

Recommended: Power Mac G4 or later

#### **Interface Support**

Ethernet 10/100BaseTX (supports TCP/IP, IPP, DHCP, BOOTP, HTTP, SNMP, SLP, LPR); Hi-Speed USB 2.0 (supports Microsoft 'Plug and Play')

#### **Paper Handling**

Standard Paper Input: 250-sheet cassette

Optional Paper Input: 500-sheet input feeder (up to two; adds legal support)

Standard Paper Output: 250-sheet face-down output tray OptionI Paper Storage: Cabinet (includes casters) Duplex Printing: manual (automatic optional)

Paper Sizes Supported:

Standard Cassette: Letter, A4, Executive, Statement, UK Quarto, Govt. Letter, A5, B5 (JIS), Kai 16, Kai 32, 16K, Japanese Postcard, Double Postcard; Monarch, Com 10, DL, B5 (ISO), C6, C5, You 4, Chou 3, and

#### **Features at a Glance**

Features	magicolor 5430 DL
Compatibility	Windows/Mac
Print Speed - Monochrome	up to 21 ppm
Print Speed - Color	up to 21 ppm
Resolution	up to 2400 dpi
Memory	64 MB (max. 576 MB)
Network Interface	1
250-Sheet Cassette	1
500-Sheet Input Feeder	m
Automatic Duplexing	m

m Optional 1 Standard

Chou 4 Envelopes; Custom sizes (W) 3.62" - 8.5" (92 - 216 mm), (L) 5.83" - 11.7" (148 - 297 mm)

Input Feeder (optional): Letter, A4, Legal, Executive, Letter Plus, Govt. Letter, Govt. Legal, Foolscap, Folio, B5 (JIS)

Duplexer (optional): Letter, Legal, A4, Executive, Folio, Foolscap, Letter Plus, Govt. Letter, Govt. Legal, B5 (JIS), Kai 16, 16K

Printable Area: .16" (4 mm) from all edges; 10.68" (271 mm) guaranteed print length standard; 13.7" (348 mm) guaranteed print length maximum (with optional

Paper Weights:

Plain paper: 16 - 24 lb. Bond (60 - 90 g/m²) Thick stock: 24 - 110 lb. Index (90 - 210 g/m2) Duplexing: 16 - 24 lb. Bond (60 - 90 g/m²)

Print Media: Plain paper, thick stock, glossy stock, OHP transparencies, laserquality labels, and envelopes. Automatic duplexing on plain paper only.

Type: Laser printer with internal controller

**Dimensions (WxDxH):** 16.7" x 20.5" x 17.3" (425 mm x 520 mm x 440 mm)  $\textbf{Weight:} \ \text{w/o consumables: } 66.4 \ \text{lbs. } (30.2 \ \text{kg}); \ \text{w/consumables: } 79.6 \ \text{lbs. } (36.2 \ \text{kg}); \ \text{w/consumables: } 10.2 \ \text{kg}; \ \text{k$ kg); as shipped: 92 lbs. (41.8 kg)

#### **Electrical**

**Power Requirements:** 

120V Model: 120 VAC  $\pm$  10%; 50/60 Hz  $\pm$  3%

220/240V Model: 220/240 VAC ± 10%, 50/60 Hz ± 3%

Power Consumption: Operating: 800 W average, 1,250 W maximum

Standby: 170 W average

Energy Star\* Compliant: 42.9 W or less

#### **Environmental**

Temperature Requirements: Operating: 50°to 95° F (10° to 35° C)

Non-operating: 32° to 95° F (0° to 35°C) Humidity: Operating: 15% to 85% RH Non-operating: 10% to 85% RH

Noise Levels: Operating: <54 dB(A); Standby: <39 dB(A)

#### **Regulatory/Safety Conformity**

UL, cUL, CSA, FCC-B, CDRH, DOC, SASO, RPC

#### **Consumables**

Printer ships with one each Cyan, Magenta, Yellow, and Black Toner Cartridges (yield up to 3,000 letter/A4 pages @ 5% coverage); Transfer Belt; Waste Toner Box

Replacement Cartridges:

Cyan, Magenta, Yellow and Black toner cartridges yield up to 6,000 letter/A4 pages @ 5% coverage

The stated life expectancy of each consumable in your printer is based on printing under specific operating conditions such as page coverage for a particular page size (5% coverage of letter/A4). The actual consumable's life will vary depending on the use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

#### **Typefaces**

Compatible with all Windows and/or TrueType® fonts printed via Windows GDI or Macintosh utilities. One (1) resident typeface included.

#### Warranty

1 year exchange

#### **KONICA MINOLTA** PRINTING SOLUTIONS U.S.A., INC. (USA, Canada, Latin America) Tel.: +1 (800) 523 2696

Fax: +1 (251) 639 4490

#### Websites:

buymagicolor.com http://printer.konicaminolta.com www.g-shopusa.com

#### PN:mc5430DLSs01\_05

Copyright © 2005 KONICA MINOLTA PRINTING SOLUTIONS U.S.A., INC. All Rights Reserved. KONICA MINOLTA and the KONICA MINOLTA logo are trademarks or registered trademarks of KONICA MINOLTA HOLDINGS, INC. magicolor is a trademark or registered trademark of KONICA MINOLTA PRINTING SOLUTIONS U.S.A., INC. PageScope is a trademark or registered trademark of KONICA MINOLTA PRINTING SOLUTIONS U.S.A., INC. PageScope is a trademark or registered trademark of KONICA MINOLTA BUSINESS TECHNOLOGIES, INC. All other trademarks or registered trademarks are the property of their respective owners. Some images provided by kind courtesy of digitalvisiononline.com.



